



Aral Getriebeöl SNA-B

High-performance transmission fluid

Description

High-performance transmission fluid with Aral Synthesis Technology for use over a wide range of temperatures in rear axles, manual gearboxes, steering systems, mainly in commercial vehicles.

Aral Getriebeöl SNA-B is designed for extended fluid-drain intervals (up to 400,000 km).

This product (Scania STO 1:0) is specifically required by Scania in rear-axle drives and manual gearboxes.

Typical Characteristics

Name	Method	Units	Aral Getriebeöl SNA-B
Density @ 15C, Relative	ASTM D4052	g/ml	0.889
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	25.7
Pour Point	ASTM D97	°C	-30
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	266
Viscosity Index	ASTM D2270	None	125
Flash Point, COC	ASTM D92	°C	238

Product Performance Claims

API GL-5

Scania STO 1:0

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral Getriebeöl SNA-B
09 Nov 2011

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft Geschäftsbereich Schmierstoffe Max-Born-Str. 2, D-22761 Hamburg
01801-11 55 11
www.aral-lubricants.de